



BATTERY OPERATED STEEL STRAPPING TOOLS

Experience Unmatched Performance with the S19 & R19 Steel Strapping Hand Tools.

The S19 and R19 set a new standard for battery-operated steel strapping, excelling in both stationary and mobile applications, even on rounded or irregular surfaces. Designed for demanding packaging tasks, they combine ergonomic comfort with advanced technology for consistent, precise, and reliable performance.

Manufactured to Swiss standards and DEKRA certified, these tools deliver exceptional strength, efficiency, and durability. They're the preferred choice for securing steel packages across industries, offering the ideal balance of power and control for any application.

Whether you need mobility or fixed-station performance, the R19 and S19 are the smart, reliable choice for organizations that demand excellence in packaging.



PROTECTIVE DESIGN



BATTERY OPERATED



TOUCH SCREEN INTERFACE



FAVOURITE PRESETS



EASY CLEANING



STRAP ALIGNMENT GUIDE



Powered by  **BOSCH**



CODE DESCRIPTION

46811 S19 Steel Strapping Battery-operated Combination Tool 19mm – Sealless

CODE DESCRIPTION

46801 R19 Steel Strapping Battery-operated Combination Tool 19mm – Single Notch Seal

MODEL	 S19 - SEALLESS STEEL STRAPPING TOOL 19mm	 R19 - SINGLE NOTCH SEAL STEEL STRAPPING TOOL 19mm
IDEAL FOR	- Stationary and offline applications. - Efficient medium-heavy duty steel strapping solutions. - Increased productivity.	- Stationary and offline applications. - Heavy duty industrial steel strapping solutions. - Increased productivity.
OPERATION MODE	Auto / Semi / Manual	Auto / Semi / Manual
TENSION FORCE RANGE	1000 – 5500 N	400 – 3000 N
TENSION SPEED	135mm/s	135mm/s
WEIGHT (INC. BATTERY)	5.4Kg	4.5Kg
DIMENSION (L X W X H)	411 x 147 x 131mm	390 x 150 x 140mm
WORKING TEMPERATURE	-10°C to +40°C	-10°C to +40°C
RELATIVE HUMIDITY	Up to 90%	Up to 90%
SEALING TYPE	Sealless Notched Joint	Single Notch

BATTERY / CHARGER		
CHARGER TYPE	Bosch	Bosch
BATTERY CHARGER VOLTAGE	100 or 110 or 230 V	100 or 110 or 230 V
CHARGING TIME	30min (80%) – 50min	30min (80%) – 50min
BATTERY TYPE (STANDARD)	Bosch Li-Ion ProCORE 18V, 4.0 Ah	Bosch Li-Ion ProCORE 18V, 4.0 Ah
CYCLES PER BATTERY CHARGE	up to 500	up to 500

STRAP STANDARD QUALITY		
STRAP WIDTH	16, 19mm	16, 19mm
STRAP THICKNESS	0,38 - 0,63mm	0,40 - 0,63mm
STRAP TENSILE STRENGTH (up to approx. N/mm ² - lbs/sq.inch)	850 (120 000)	850 (120 000)

STRAP HIGH TENSILE QUALITY		
STRAP THICKNESS	0,38 - 0,63mm	0,40 - 0,63mm
STRAP TENSILE STRENGTH (up to approx. N/mm ² - lbs/sq.inch)	1100 (157000)	1100 (157000)
MATCHING SEALS	N/A	16, 19mm (5/8", 3/4")